

Specifications

LS-100, 60 HZ

Compressor Performance

Model	25L	25H	25HH	25XH	30L	30H	30HH	30XH	40L	40H	40HH	40XH
Capacity (acfm)	119	106	95	85	134	127	111	103.5	169	163	147	130
Full Load Pressure (psig)	100	125	150	175	100	125	150	175	100	125	150	175
Motor (hp)	25	25	25	25	30	30	30	30	40	40	40	40

Dimensions and Weight (Enclosure) Air-Cooled

Length (in)	57 (60)				57 (60)				58.6 (66)			
Width (in)	34 (36)				34 (36)				34 (36)			
Height (in)	39 (42)				39 (42)				39 (42)			
Weight (lb)	990 (1240)				1015 (1265)				1115 (1400)			

Measured in accordance with the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217) at full operating pressure.
All compressors tested at full operating pressure to meet the CAGI/PNEUROP standard.

MAXIMIZE YOUR COMPRESSED AIR SYSTEM



This compressor is one of several compressed air products that comprise the Sullair System. The System includes oil-free and lubricated compressors, compressed air dryers, filters and other related contaminant-removal accessories working together to deliver superior performance and energy efficiency.



Moisture Removal



Particulate Removal



Condensate Separation



Condensation Removal



To help compressed air users reduce their energy costs and improve their productivity, Sullair offers AirMetrix solutions to analyze, manage and control total compressed air systems. AirMetrix solutions include: energy efficiency products, compressed air system controls, monitoring and management systems, air distribution products, and air system audits.



www.sullair.com

SULLAIR CORPORATION, 3700 E. Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-367-6737 or 1-219-879-5451