

Specifications

LS-120, 60 HZ

Compressor Performance

Model	40L	40H	40HH	50L	50H	50HH	50XH	60H	60HH	60XH
Capacity (acfm)	199	183	166	245	221	197	180	264	243	218
Full Load Pressure (psig)	100	125	150	100	125	150	175	125	150	175
Motor (hp)	40	40	40	50	50	50	50	60	60	60

Dimensions and Weight (Enclosure) Air-Cooled

Length (in)	72 (72)			72 (72)			72 (72)		
Width (in)	48 (48)			48 (48)			48 (48)		
Height (in)	60 (62.5)			60 (62.5)			60 (62.5)		
Weight (lb)	2270 (2660)			2300 (2690)			2500 (2890)		

LS-160, 60 HZ

Compressor Performance

Model	60L	60H	60HH	75L	75H	75HH	75XH	100L	100H
Capacity (acfm)	304	262	235	377	346	298	278	489	447
Full Load Pressure (psig)	100	125	150	100	125	150	175	100	125
Motor (hp)	60	60	60	75	75	75	75	100	100

Dimensions and Weight (Enclosure) Air-Cooled

Length (in)	72 (72)			72 (72)			72 (78)		
Width (in)	48 (48)			48 (48)			48 (48)		
Height (in)	60 (62.5)			60 (62.5)			59 (62.3)		
Weight (lb)	2690 (3180)			2720 (3210)			2740 (3410)		

Measured in accordance with the CAGI/PNEURO P22CPTC2 Test Code (Annex C to ISO 1217) at full operating pressure.
All compressors tested at full operating pressure to meet the CAGI/PNEURO standard.

MAXIMIZE YOUR COMPRESSED AIR SYSTEM



This compressor is one of several compressed air products that comprise the Sullair System. The System includes oil-free and lubricated compressors, compressed air dryers, filters and other related contaminant-removal accessories working together to deliver superior performance and energy efficiency.



Moisture Removal



Particulate Removal



Condensate Separation



Condensation Removal



To help compressed air users reduce their energy costs and improve their productivity, Sullair offers AirMetrix solutions to analyze, manage and control total compressed air systems. AirMetrix solutions include: energy efficiency products, compressed air system controls, monitoring and management systems, air distribution products, and air system audits.



www.sullair.com

SULLAIR CORPORATION, 3700 E. Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-367-6737 or 1-219-879-5451