

SPECIFICATIONS

Specifications for LS-25S 60Hz

	250L	250H	300L	300H	350L	350H
Compressor Performance						
Capacity (acfm)	1218	1075	1480	1330	1615	1460
Full Load Pressure (psig)	100	125	100	125	100	125
Motor (hp)	250	250	300	300	350	350
Dimensions and Weight, Enclosure, Air-Cooled						
Length (in)	154	154	154	154	154	154
Width (in)	78	78	78	78	78	78
Height (in)	86	86	86	86	86	86
Weight (lb)	10760	10760	10760	10760	11110	11110


Specifications for LS-25SKT 60Hz

	250L	250H	300L	300H	350L	350H
Compressor Performance						
Capacity (acfm)	1218	1075	1480	1330	1615	1460
Full Load Pressure (psig)	100	125	100	125	100	125
Motor (hp)	250	250	300	300	350	350
Dimensions and Weight, Enclosure, Air-Cooled						
Length (in)	154	154	154	154	154	154
Width (in)	78	78	78	78	78	78
Height (in)	86	86	86	86	86	86
Weight (lb)	10760	10760	10760	10760	11110	11110

Sullair is committed to a program of continuous improvement. Features and specifications may change without notice.



This is one of several compressed air products that comprise the Sullair System. The System includes oil-free and lubricated air compressors, dryers, filters and related accessories, designed to deliver peak performance and energy efficiency.



www.sullair.com

SULLAIR CORPORATION, 3700 E. Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-367-6737 or 219-879-5451

SIP-6000 Specifications subject to change without notice. © Copyright 2003 Sullair Corporation. All rights reserved. E/5/03/5



Printed on recycled paper.