

## Specifications for TS-20 60Hz

	100L	100H	125L	125H	125HH	125XH	150L	150H	150HH	150XH	200L	200H	200HH	200XH
<b>Compressor Performance</b>														
Capacity (acfm)	575	500	680	615	575	500	826	763	680	616	1035	960	826	776
Full Load Pressure (psig)	100	125	100	125	150	175	100	125	150	175	100	125	150	175
Motor (hp)	100	100	125	125	125	125	150	150	150	150	200	200	200	200
<b>Dimensions and Weight, Enclosure, Air-Cooled</b>														
Length (in)	120	120	120	120	120	120	120	120	120	120	120	120	120	120
Width (in)	72	72	72	72	72	72	72	72	72	72	72	72	72	72
Height (in)	68	68	68	68	68	68	68	68	68	68	68	68	68	68
Weight (lb)	8100	8100	8200	8200	8200	8400	8400	8400	8400	8400	8600	8600	8600	8600

## Specifications for TS-20KT 60Hz

	100L	100H	125L	125H	150L	150H	200L	200H
<b>Compressor Performance</b>								
Capacity (acfm)	575	500	680	615	826	763	1035	960
Full Load Pressure (psig)	100	125	100	125	100	125	100	125
Motor (hp)	100	100	125	125	150	150	200	200
<b>Dimensions and Weight, Enclosure, Air-Cooled</b>								
Length (in)	120	120	120	120	120	120	120	120
Width (in)	72	72	72	72	72	72	72	72
Height (in)	68	68	68	68	68	68	68	68
Weight (lb)	8100	8100	8200	8200	8400	8400	8600	8600

Sullair is committed to a program of continuous improvement. Features and specifications may change without notice. Consult your Sullair representative or authorized Sullair distributor.

## Specifications for TS-32 60Hz

	200L	250L	250H	250HH	300L	300H	300HH	300XH	350L	350H	350HH	350XH	350ZH
<b>Compressor Performance</b>													
Capacity (acfm)	1105	1335	1240	1100	1640	1440	1330	1240	1875	1733	1575	1440	1330
Full Load Pressure (psig)	100	100	125	150	100	125	150	175	100	125	150	175	200
Motor (hp)	200	250	250	250	300	300	300	300	350	350	350	350	350
<b>Dimensions and Weight, Enclosure, Air-Cooled</b>													
Length (in)	154	154	154	154	154	154	154	154	154	154	154	154	154
Width (in)	78	78	78	78	78	78	78	78	78	78	78	78	78
Height (in)	86	86	86	86	86	86	86	86	86	86	86	86	86
Weight (lb)	12480	12720	12720	12720	13270	13270	13270	13270	13620	13620	13620	13620	13620

## Specifications for TS-32KT 60Hz

	200L	250L	250H	300L	300H	350L	350H
<b>Compressor Performance</b>							
Capacity (acfm)	1105	1335	1240	1640	1440	1875	1733
Full Load Pressure (psig)	100	100	125	100	125	100	125
Motor (hp)	200	250	250	300	300	350	350
<b>Dimensions and Weight, Enclosure, Air-Cooled</b>							
Length (in)	154	154	154	154	154	154	154
Width (in)	78	78	78	78	78	78	78
Height (in)	86	86	86	86	86	86	86
Weight (lb)	12480	12720	12720	13270	13270	13620	13620

Sullair is committed to a program of continuous improvement. Features and specifications may change without notice. Consult your Sullair representative or authorized Sullair distributor.

## Specifications for TS-32S 60Hz

	400L	400H	400HH	450L	450H	450HH	500L	500H	500HH	600L	600H	600HH
<b>Compressor Performance</b>												
Capacity (acfm)	2200	1943	1681	2350	2135	1943	2530	2350	2220	3000	2700	2530
Full Load Pressure (psig)	100	125	150	100	125	150	100	125	150	100	125	150
Motor (hp)	400	400	400	450	450	450	500	500	500	600	600	600
<b>Dimensions and Weight, Enclosure, Air-Cooled</b>												
Length (in)	175	175	175	175	175	175	175	175	175	175	175	175
Width (in)	84	84	84	84	84	84	84	84	84	84	84	84
Height (in)	93	93	93	93	93	93	93	93	93	93	93	93
Weight (lb)	15900	15900	15900	15900	15900	15900	16400	16400	16400	16400	16400	16400

## Specifications for TS-32SKT 60Hz

	400L	400H	450L	450H	500L	500H	600L	600H
<b>Compressor Performance</b>								
Capacity (acfm)	2200	1943	2350	2135	2530	2350	3000	2700
Full Load Pressure (psig)	100	125	100	125	100	125	100	125
Motor (hp)	400	400	450	450	500	500	600	600
<b>Dimensions and Weight, Enclosure, Air-Cooled</b>								
Length (in)	175	175	175	175	175	175	175	175
Width (in)	84	84	84	84	84	84	84	84
Height (in)	93	93	93	93	93	93	93	93
Weight (lb)	15900	15900	15900	15900	16400	16400	16400	16400

Sullair is committed to a program of continuous improvement. Features and specifications may change without notice. Consult your Sullair representative or authorized Sullair distributor.



This is one of several compressed air products that comprise the Sullair System. The System includes oil-free and lubricated air compressors, dryers, filters and related accessories, designed to deliver peak performance and energy efficiency.



Sullair is pleased to be ISO 9001 certified by Lloyd's Register Quality Company



[www.sullair.com](http://www.sullair.com)

SULLAIR CORPORATION, 3700 E. Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-367-6737 or 219-879-5451

SIP-7000 Specifications subject to change without notice. © Copyright 2003 Sullair Corporation. All rights reserved. E/1/03/6.5



Printed on recycled paper.