

Standard features and options

| | VCC-200/100 HP | VCC-200S/125-150 HP |
|--|----------------|---------------------|
| Sullair Supervisor Controller | ● | ● |
| Direct Coupled | ● | ● |
| Highly Efficient Air/Fluid Separation | ● | ● |
| Fiberglass Fluid Filter | ● | ● |
| Heavy Duty Intake Filter | ● | ● |
| Sullube 8000 Hour Compressor Fluid | ● | ● |
| Food Grade Compressor Fluid | ● | ● |
| Optimizer Separator | ● | ● |
| Bearing Fluid Reservoir | ● | ● |
| Wye Delta Starter | ● | ● |
| Solid State Starter | ● | ● |
| Full Voltage Starter | ● | ● |
| ODP Premium Efficiency Motor | ● | ● |
| TEFC Premium Efficiency Motor | ● | ● |
| Totally Enclosed Fan Motor | ● | ● |
| Emerald 5-year Health Assurance ⁽¹⁾ | ● | ● |
| 24KT (10-Year Air End Warranty) ⁽²⁾ | ● | ● |
| Sound Attenuating Enclosure | ● | ● |
| Sullair's Versatile Control System | ● | ● |
| Cold Weather Package | ● | ● |
| SCD Zero Air Loss Condensate Drain | ● | ● |
| Energy Efficiency System | ● | ● |

● = Standard ● = Option

(1) Sullair's 5-year warranty includes air end, motor, air/fluid receiver and cooler(s). "L" and "H" models only.
 (2) Sullair's 24KT warranty includes 5-years on the motor, air/fluid receiver and cooler(s). "L" and "H" models only.

Specifications

| VCC-200 | 100L | 100H | | | | | | |
|---|------|------|--------|--------|------|------|--------|--------|
| Compressor Performance | | | | | | | | |
| Full Load Pressure (psig) | 100 | 125 | | | | | | |
| Capacity (acfm) | 511 | 468 | | | | | | |
| Motor (hp) | 100 | 100 | | | | | | |
| Dimensions and Weights, Enclosure-Air-Cooled | | | | | | | | |
| Length (in) | 88 | 88 | | | | | | |
| Width (in) | 48 | 48 | | | | | | |
| Height (in) | 61.5 | 61.5 | | | | | | |
| Weight (lb) | 4250 | 4250 | | | | | | |
| VCC-200S | 125L | 125H | 125HH* | 125XH* | 150L | 150H | 150HH* | 150XH* |
| Compressor Performance | | | | | | | | |
| Full Load Pressure (psig) | 100 | 125 | 150 | 175 | 100 | 125 | 150 | 175 |
| Capacity (acfm) | 647 | 587 | 506 | 457 | 752 | 683 | 631 | 570 |
| Motor (hp) | 125 | 125 | 125 | 125 | 150 | 150 | 150 | 150 |
| Dimensions and Weights, Enclosure-Air-Cooled | | | | | | | | |
| Length (in) | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 |
| Width (in) | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 60 |
| Height (in) | 68 | 68 | 68 | 68 | 68 | 68 | 68 | 68 |
| Weight (lb.) | 5250 | 5250 | 5250 | 5250 | 5570 | 5570 | 5570 | 5570 |

* HH and XH Models not available with 24KT.



Sullair is pleased to be ISO 9001 certified by Lloyd's Register Quality Company



www.sullair.com

SULLAIR CORPORATION, 3700 E. Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-367-6737
 SIP-1000 Specifications subject to change without notice. © Copyright 2004 Sullair Corporation. All rights reserved. E/01/04/10

© The color green is a registered trademark of Sullair Corporation.



Printed on recycled paper.